

PRODUCT-DETAILS

CR-MX024DC2T

CR-MX024DC2T Pluggable interface relay 2c/o, A1-A2=24VDC, 250V/7A, test button



General Information

| | |
|-----------------------|---|
| Extended Product Type | CR-MX024DC2T |
| Product ID | 1SVR405641R1000 |
| EAN | 4013614536014 |
| Catalog Description | CR-MX024DC2T Pluggable interface relay 2c/o, A1-A2=24VDC, 250V/7A, test button |
| Long Description | The CR-MX024DC2T pluggable interface relay is from the CR-MX (miniature) relay range. This relay operates with a 24 V DC rated control supply voltage and has a 2 c/o (SPDT) output with contacts rated at 250 V / 7 A. The relay has an integrated blue test button for manual actuation and locking of the output contacts. Standard sockets, pluggable function modules, holders and markers are available as accessories. |

Ordering

| | |
|------------------------|---------------|
| EAN | 4013614536014 |
| Minimum Order Quantity | 300 piece |
| Customs Tariff Number | 85364900 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CDC117020D0201 |
| Instructions and Manuals | 1SVC405631M9000 |
| CAD Dimensional Drawing | 2CDC001079B0201 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 21.5 mm |
| Product Net Height | 37 mm |
| Product Net Depth / Length | 28 mm |
| Product Net Weight | 0.034 kg |

Technical

| | |
|--|---|
| Function | Pluggable miniature interface relay CR-MX |
| Rated Control Supply Voltage (U_s) | 24 V DC |
| Rated Operational Voltage | 250 V AC |
| Output | 2 c/o (SPDT) contacts |
| Output Signal | 250 V / 7 A |
| Terminal Type | Flat-Pin Connections |
| Rated Operational Current AC-12 (I_{θ}) | (230 V) 7 A |
| Rated Operational Current AC-15 (I_{θ}) | (120 V) 2 A (230 V) 0.8 A |
| Rated Operational Current DC-12 (I_{θ}) | (24 V) 7 A |
| Rated Operational Current DC-13 (I_{θ}) | (24 V) 1.9 A (120 V) 0.8 A |
| Rated Impulse Withstand Voltage (U_{imp}) | Between Coil and Contacts 1.5 kV |
| Rated Insulation Voltage (U_i) | 250 V |
| Degree of Protection | IP40 |
| Mounting Position | 1 |
| Standards | CSA 22.2 No. 14 IEC/EN 63000 IEC/EN 61010-1 UL 508 |

Technical UL/CSA

| | |
|----------------------------------|----------|
| Maximum Operating Voltage UL/CSA | 250 V AC |
| Flammability According to UL94 | V-2 |

Environmental

| | |
|--|--|
| Ambient Air Temperature | Operation -40 ... +70 °C Storage -40 ... +70 °C |
| Maximum Operating Altitude Permissible | Without Derating 2000 m |
| RoHS Information | 1SVD982022-0002 |
| RoHS Status | Following EU Directive 2011/65/EU |

Certificates and Declarations

| | |
|--------------------------------|-----------------|
| CQC Certificate | CQC_14002105209 |
| cUR Certificate | cUR_E244330 |
| Declaration of Conformity - CE | 1SVD982022-0003 |
| TÜV Certificate | TUEV_R50275618 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 10 piece |
| Package Level 1 Width | 103 mm |
| Package Level 1 Depth / Length | 142 mm |
| Package Level 1 Height | 37 mm |
| Package Level 1 Gross Weight | 0.42 kg |
| Package Level 1 EAN | 4013614536366 |
| Package Level 2 Units | box 300 piece |
| Package Level 2 EAN | 4013614540370 |

Classifications

| | |
|----------------------------|----------------------------|
| Object Classification Code | K |
| ETIM 7 | EC001437 - Switching relay |
| ETIM 8 | EC001437 - Switching relay |
| ETIM 9 | EC001437 - Switching relay |
| eClass | V11.0 : 27371601 |
| UNSPSC | 39122331 |

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Interface Relays and Optocouplers

